

An Adande Compact unit provides convenient storage right where you need it, next to griddle and fry stations. Compacts have many other uses, from refrigerated vegetable and salad storage to delicate frozen desserts, and being small and easy to move, are ideal for outside catering. Compacts have the same chill to frozen flexibility as standard Adande Drawers

It's an Adande®; it works like no other fridge or freezer...

ADANDE® Compact Unit



Applications

- At the griddle for burgers, etc.
- At the fry station for fries, etc.
- Ice cream and ices
- Upright bottle storage
- Mobile catering

Operational Benefits

- Flexibility: works as fridge or freezer
- Blast chiller option also available
- Reliable: amazing temperature stability
- Green: extremely energy efficient
- Cuts food wastage
 - » Food does not dehydrate
 - » No freezer burn or ice crystals
 - » No condensation on the food
- Ergonomically efficient
- Minimal maintenance costs
- Quick and easy to clean
- Robust and reliable



CaterQuotes



Tel: +44 (0) 844 376 0023 | Fax: +44 (0) 1502 533794 | Email: info@adande.com | www.adande.com

COMPACT DRAWER UNITS



VCC - REAR ENGINE COMPACT


Fridge or Freezer.
Each drawer is switchable in minutes.
Accurate and stable at any temperature.
(-22°C to +15°C)



Information

Just 450 mm wide, Adande® Compact units provide convenient storage next to griddle and fry stations.

Compacts have many other uses, from refrigerated upright bottle storage to frozen ices and, being small and easy to move, are ideal for outside catering.



Drawer Storage Capacity

1 x 1/1 GN Pan 200 mm Deep at the bottom

1 x 1/1 GN Pan 100 mm Deep on top

Code	Type	Fin Height	Wt. Loading
VCC1/DCT	COVER TOP & DOUBLE CASTORS	845 mm	0 kg
VCC1/GCW	SOLID TOP & STANDARD CASTORS	900 mm	300 kg
VCC1/HCW	SOLID TOP & HIGH CASTORS	948 mm	300 kg
R2	REFRIGERANT R600		
R1	REFRIGERANT R404a		

BLAST CHILL OPTION IS NOT AVAILABLE ON COMPACT (VCC) UNITS

COMPACT UNITS HAVE THE SAME FRIDGE TO FREEZER FLEXIBILITY AS STANDARD SIZE ADANDE® DRAWERS

CLIMATE TESTING: Tested to Climate Standard 5 (40°C and 40% relative humidity)
MAINS: 230 Vac 50 Hz also 60 Hz available