

Applications

- Bulk storage at point-of-use
- Chef Base plus standard Heat Shield
- Choice of worktop heights
- Robust equipment drawers
- In-range cassette drawer
- Holds set temp point in hot kitchens
- Hot or Cool cookline applications

Operational Benefits

- Flexibility: works as fridge or freezer
- Blast chiller option also available
- Reliable: amazing temperature stability
- Green: extremely energy efficient
- Cuts food wastage
 - » Food does not dehydrate
 - » No freezer burn or ice crystals
 - » No condensation on the food
- Ergonomically efficient
- Minimal maintenance costs
- Quick and easy to clean
- Robust and reliable

It's an Adande®; it works like no other fridge or freezer...

ADANDE® in the Cookline



Available on
CaterQuotes



Centre: 2 Stack Adande® in the Cookline
Bottom Left: Cassette Drawer incorporated in Cooker Range
Bottom Right: Adande® under Griddle

CHEF BASE UNITS - HOT AND COOL COOKLINE APPLICATIONS



VCS - SIDE ENGINE

Storage Capacity per Drawer

4 x 1/1 GN Pans
100 mm Deep
or equivalent


Fridge or Freezer
Each drawer is
switchable in minutes.
Accurate and stable at
any temperature
(-22°C to +15°C)



VCR - REAR ENGINE

Information


Heat Shield (HS) worktops can be extended, to accommodate larger items of cooking equipment, and/or to provide a storage void under the worktop



Adande® Chef Bases with heat shield (HS) worktops are designed to accommodate hot cooking equipment, and withstand temperatures up to 200°C.

Chef Bases can be supplied with a variety of castors and rollers to achieve specific worktop heights and cooking equipment weight loadings.

These units can also be fitted with fixed frames (FF) where a particular worktop finished height, between 590 and 900 mm, is required.



Solid Worktops (W) can be extended to accommodate larger items of equipment, and/or to provide a storage void under the worktop

List Prices

Code	Type	Height TTS	Wt. Loading
VCS1/HCHS	HIGH CASTORS	616 mm	235 kg
VCS1/CHS	STANDARD CASTORS	545 mm	300 kg
VCS1/RHS	ROLLERS & FEET	501 mm	285 kg
VCS1/SRHS	SMALL ROLLERS & FEET	491 mm	285 kg
VCS1/FFHS	FIXED FRAME	590-900 mm	235 kg
BC	BLAST CHILL AVAILABLE ON ALL UNITS ABOVE		
R2	HYDROCARBON OPTION AVAILABLE ON ALL UNITS ABOVE		

Code	Type	Height TTS	Wt. Loading
VCR1/HCHS	HIGH CASTORS	616 mm	235 kg
VCR1/CHS	STANDARD CASTORS	545 mm	300 kg
VCR1/RHS	ROLLERS & FEET	501 mm	285 kg
VCR1/SRHS	SMALL ROLLERS & FEET	491 mm	285 kg
VCR1/FFHS	FIXED FRAME	590-900 mm	235 kg
R2	HYDROCARBON OPTION AVAILABLE ON ALL UNITS ABOVE		

HYDROCARBON UNITS USE 19% LESS ENERGY THAN DRAWERS RUNNING ON HFC REFRIGERANT IN FREEZER MODE
BLAST CHILL OPTION IS NOT AVAILABLE ON REAR ENGINE (VCR) UNITS