

SMF IC600

SYSTEM PART:	#80-6100
REPLACEMENT CARTRIDGE:	#108-010
RATED CAPACITY (GALLONS)	CHLORINE *: 50,000 CHLORAMINE*: 7,000
FLOW RATE:	2.5 GPM
MIN./MAX. PRESSURE:	40–125 PSI
MIN./MAX. TEMP.:	40°–100° F
INLET/OUTLET SIZE:	1/2" BARB STANDARD
	17 MODULAR FITTINGS AVAILABLE
SHIPPING WEIGHT:	16 LBS.
DIMENSIONS (W/D/H):	14/9/19"

FOUNTAIN APPLICATION

FOR: CHLORINE, CHLORAMINE, SEDIMENT, THMS, ORGANICS, TANNINS, BAD TASTE AND ODOR REDUCTION

VOLUME: MEDIUM



SPECIFIED TO:

- IMPROVE TASTE OF FOUNTAIN BEVERAGES
- PROVIDE SAFE, CLEAN INGREDIENT WATER
- REDUCE CHLORINE, CHLORAMINE, BAD TASTES AND ODORS, TOTAL ORGANIC COMPOUNDS, TANNINS AND TRIHALOMETHANES
- INCREASE FOUNTAIN SALES
- INCREASE CARBONATION

FILTER BENEFITS:

- ONE FILTER CAN DO IT ALL: DIRT REDUCTION, CHEMICAL REDUCTION AND CHLORAMINES REDUCTION! NO PRE-FILTER REQUIRED!
- THE FIRST JUMBO SANITARY FILTER ON THE MARKET!
- NYLON CONSTRUCTION TO WITHSTAND HIGH PRESSURE!
- FILTER PERFORMANCE GUARANTEE!
- 40 TIMES MORE DIRT HOLDING CAPACITY THAN CONVENTIONAL CARBON BLOCK FILTERS AND OTHER POLYPROPYLENE SEDIMENT FILTERS!
- 30 TIMES THE CHLORAMINE REDUCTION OF A CONVENTIONAL CARBON BLOCK!
- LOW PRESSURE DROP!
- MODULAR FILTER DESIGN FOR UP TO 50% LESS INSTALLATION TIME!
- QUICKLY ADD FITTINGS FOR EXTRA FILTER CAPACITY WITH NO TOOLS REQUIRED!

TECHNOLOGY:

- ULTRA HIGH POROSITY CARBON WITH MICRO-STRUCTURE

APPLICATIONS:

- 1 CARBONATOR
- FOUNTAIN AND MULTIUSE APPLICATION SUCH AS COFFEE, TEA AND JUICE

* Independently tested to NSF/ANSI Standard 42 specifications for the reduction of Chlorine and Chloramine.



SMF IC600 has been tested and certified by NSF International against NSF/ANSI Std. 42 for the reduction of Chlorine, Taste and Odor, and Particulate Class I, 0.5-1 µm. Please visit www.nsf.org for specifications. Do not use with water that is microbiologically unsafe or of unknown quality.

selecto

3980 LAKEFIELD COURT, SUWANEE, GA 30024 USA
800-635-4017 • 678-475-0799 • WWW.SELECTOINC.COM

© 2008 Selecto Scientific, Inc. • All Rights Reserved.

805-001 Rev. 10-15-08

IC600+

System Part Number: 90-0600
Replacement Cartridge: 108-010NS

APPLICATIONS

Function: Taste, Odor, Scale
Ice + Brewed Beverages + Fountain + Drinking
Steamers: Water

PERFORMANCE

Particulate Rating (microns): 0.0125
Initial Pressure Loss (psi): 1.0-5.0
Chlorine Reduction (gal/gpm): 50,000/5.0
Chloramine Reduction (gal/gpm): 15,000/5.0

SPECIFICATIONS

Head Configuration: Single
Temperature (F): 40-100
Pressure (psi): 30-100
Height (inches): 19
Width (inches): 14
Depth (inches): 09
Shipping Weight (lbs): 13

TECHNOLOGY

Filter Housing: Polypropylene
Cartridge Housing: Reinforced Nylon
Media: Hollow Carbon