



Salad Prep. Tables



• B090B-1ROOS-E



• B120B-2RROS-E



• B150B-2RROS-E



• B180B-3RRRS-E

Cabinet Construction

Heavy duty 430 stainless steel, and galvanized steel finished bottom and back wall of exterior. High quality 445NF stainless steel interior, 304 stainless steel worktop, ABS evaporator drain cover. Insulated with 2.5" thick high density foamed-in-place polyurethane foam. Four 3" diameter casters (front casters with brakes). Door heater installed around inside cabinet frame to prevent moisture build up.

Refrigeration System

- Side mounted condensing unit for bigger compartment use compared to back mounted units.
- Oversized condenser and evaporator coil cools to set temperature in a minimum time period and maintains it.
- Removable side panel and slide-out condensing unit for convenient repair and maintenance.
- Environmentally friendly CFC free R-134A.
- Air defrost, temperature initiated and terminated.
- Copper tube and aluminum fin evaporator with anti-corrosive coating.
- Energy efficient condensate drain pan assembly heated by high side anti-corrosive copper tube.

Doors

- 445NF stainless steel exterior and interior.
- Insulated with 2.5" thick foamed-in-place polyurethane foam.
- Rounded corners for a sleek and modern appearance.
- Heavy duty adjustable torsion spring self-closing door system.
- One piece snap-in magnetic door gasket for easy replacement.
- Heavy duty recessed door handles that stay out of the way.

Preparation Area

- Removable and adjustable sanitary 230mm cutting board (Order Manufacturing).
- Sanitary PVC pans.

Shelving

- Two epoxy coated wire shelves per section.
- 304 stainless steel pilasters and shelf clips.

Temperature Control

- Factory preset temperature, 4°C.
- Setting temperature range from 0°C to 5°C.
- Easy to read digital temperature display.
- Easy to control temperature by simply pushing buttons on control box.
- Microchip digital monitoring system provided with various functions for monitoring and maintaining ideal temperature.



Model	Ref/ Fzr/ Dual	HP	Refrigerant	# of Shelves	# of Pans	Amps (A)	Exterior Dimensions L x D x H (mm) * Height 4" include caster.	R Ref F Fzr
B090B-1ROOS-E	Ref	1/4	R-134A	2	1/6 x 12	1.88	900 x 700 x 840	R
B120B-2RROS-E	Ref	1/4	R-134A	4	1/6 x 18	2.23	1200 x 700 x 840	RR
B150B-2RROS-E	Ref	1/4	R-134A	4	1/6 x 24	2.25	1500 x 700 x 840	RR
B180B-3RRRS-E	Ref	1/3	R-134A	4	1/6 x 30	2.63	1800 x 700 x 840	RRR